

M.V. GLOBETROTTER

SHIP'S PARTICULARS

Port of Registry	VALLETTA			Nationality	MALTESE			
Call Sign	9HFK9			Class	BUREAU VERITAS			
IMO Number	9241255			Builder	NANTONG COSCO KHI SHIP ENGINEERING CO. LTD.			
Official Number	9241255			Date Keel Laid	28-Jul-2000			
Type of Ship	BULK CARRIER			Vsl Delivered	12-Jan-2001			
LOA	187.5 M / 615.16 FT		Breadth Moulded	31.00 M / 101.71 FT		International GRT	27.198	
LBP	179.00 M / 587.27 FT		Depth Moulded	16.75 M / 54.95 FT		International NRT	15.365	
			Air Draft	45.02 M / 147.71 FT		Summer DWT	48.911	
Suez Canal GRT / NRT	28,529.05 / 26,127.05			Panama Canal GRT / NRT	28,529.05 / 26,127.06			
			Displacement	Draft	Freeboard	TPC		
Light Ship			8.395 mt	3,103 m	13,689 m	45,80 mt		
Winter DWT	47.710 mt		56.105 mt	11,722 m	5,070 m	52,20 mt		
Summer DWT	48.911 mt		57.306 mt	11,971 m	4,821 m	52,20 mt		
Tropical DWT	50.212 mt		58.607 mt	12,220 m	5,572 m	52,20 mt		
Fresh Water DWT	50.351 mt		58.746 mt	12,245 m	4,547 m	52,20 mt		
Tropical Fresh DWT	51.644 mt		60.039 mt	12,494 m	4,298 m	52,30 mt		
HOLDS CAPACITY				STRENGTH (mt/sqm)				
grain (cbft)	grain (cbm)	bale (cbft)	bale (cbm)		Hatch Cover	Tank Top	Upper Deck	Max Load WT
369.642,1	10.467,1	349.188,0	9.887,9	HOLD 1	2,00	23,00	3,50	8.946 mt
454.538,6	12.871,1	431.719,0	12.224,9	HOLD 2	2,00	16,00	3,50	10.996 mt
423.267,5	11.985,6	403.195,0	11.417,2	HOLD 3	2,00	23,00	3,50	10.239 mt
442.973,1	12.543,6	420.733,0	11.913,8	HOLD 4	2,00	16,00	3,50	10.718 mt
408.735,5	11.574,1	356.937,0	10.107,3	HOLD 5	2,00	23,00	3,50	9.892 mt
2.099.156,8	59.441,5	1.961.772,0	55.551,1	TOTAL	Vessel strengthened for heavy cargoes in holds 1, 3 & 5			1, 3 & 5
				Holds may be emptied:				2 & 4
TANK TOP DIMENSIONS				HATCHES DIMENSIONS				
	breadth (fwd)	breadth (aft)	length	Hatch 1	17.01 m x 16.00 m	Hatch 4	20.25 m x 16.00 m	
hold 1	6,00 m	22,50 m	28,20 m	Hatch 2	20.25 m x 16.00 m	Hatch 5	20.25 m x 16.00 m	
hold 2	22,50 m	22,50 m	28,80 m	Hatch 3	20.25 m x 16.00 m			
hold 3	22,50 m	22,50 m	27,20 m	Cargo Holds Height	15.06 mtrs			
hold 4	22,50 m	22,50 m	28,20 m	TYPE OF HATCH COVER				
hold 5	22,50 m	9,00 m	28,20 m	MCGREGOR ELECTRO-HYDRAULIC FOLDING SINGLE TYPE				
MAIN ENGINE			CRANES		GRABS (4) FOUR			
Type	MAN-B & W 6550MC		MCGREGOR GL3026 - 4 PCS		Type	PEINER MZGL13000-6-B		
M.C.R.	6880 KW X 102.0 RPM		SWL 30/24 MT, REACH 3.2-26 M		Capacity	6 cbm / 13 cbm		
N.C.R.	6190 KW X 98.0 RPM		Max outreach from vsl's side : 9.5 m		Max SWL	15,000 kg		
DISTANCES			TANKS CAPACITY					
FWD TO BRIDGE	158.6 M / 520.2 FT		HFO (90%)	1642 CBM	Ballast	28,002 cbm, incl. Hold No. 3 - 12018 cbm		
BRIDGE TO AFT	28.9 M / 94.8 FT		MDO (90%)	106 CBM	Fresh Water	330.0 cbm		